

BANCHI PASTICCERIA

PASTRY BENCH



DELUXE 92 PSV

Banco pasticceria quattro lati vetro ventilato, porte scorrevoli. 2 Ripiani.
Ventilated positive four-sided glass pastry bench, sliding doors. 2 Shelves.

DELUXE 122 PSV

Banco pasticceria quattro lati vetro ventilato, porte scorrevoli. 2 Ripiani.
Ventilated positive four-sided glass pastry bench, sliding doors. 2 Shelves.

DELUXE 152 PSV

Banco pasticceria quattro lati vetro ventilato, porte scorrevoli. 2 Ripiani.
Ventilated positive four-sided glass pastry bench, sliding doors. 2 Shelves.





Ripiani: vetro temperato, frontale acciaio
Shelves: tempered glass, stainless steel front



Termostato elettronico
Electronic thermostat



Esterno acciaio specchiato, vetro lucido nero
Body mirror stainless steel, black shiny mirror



Dimensioni mm / Dimensions mm	DELUXE 92 PSV	DELUXE 122 PSV	DELUXE 152 PSV
Dimensioni Esterne (LxPxH) / External Dimensions (WxDxH)	900 x 740 x 1200	1200 x 740 x 1200	1500 x 740 x 1200
Dimensioni Imballo (LxPxH) / Packaging Dimensions (WxDxH)	980 x 830 x 1350	1280 x 830 x 1350	1580 x 830 x 1350
A - Larghezza / Width	840	1140	1440
B - Profondità / Depth	630	630	630
C - Altezza / Height	690	690	690

Caratteristiche Tecniche / Technical Features	DELUXE 92 PSV	DELUXE 122 PSV	DELUXE 152 PSV
Temperatura / Temperature Range	+2 °C / +10 °C	+2 °C / +10 °C	+2 °C / +10 °C
Classe Climatica / Climate Class	4	4	4
Volume Netto-Lordo / Net-Gross Volume	Lt. 370 / 415	Lt. 495 / 555	Lt. 620 / 700
Superficie Esterna Body	Acciaio AISI 304 Stainless steel AISI 304	Acciaio AISI 304 Stainless steel AISI 304	Acciaio AISI 304 Stainless steel AISI 304
Superficie Interna Inner Liner	Acciaio AISI 304 Stainless steel AISI 304	Acciaio AISI 304 Stainless steel AISI 304	Acciaio AISI 304 Stainless steel AISI 304
Termostato / Thermostat	Elettronico / Electronic	Elettronico / Electronic	Elettronico / Electronic
Smart Link WiFi Controllo remoto / Remote controller	Optional	Optional	Optional
Rumorosità / Noise level	dB 58	dB 61	dB 67
Spessore isolamento / Insulation thickness	mm 45	mm 45	mm 45
Sbrinatorio Defrost	Automatico a fermo compressore Automatic compressor cycle	Automatico a fermo compressore Automatic compressor cycle	Automatico a fermo compressore Automatic compressor cycle
Illuminazione / Lighting	3 Led orizzontali / Horizontal	3 Led orizzontali / Horizontal	3 Led orizzontali / Horizontal
Mensole in vetro temperato (LxP) Tempered glass shelves (WxD)	N°1 mm 738 x 278 N°1 mm 738 x 318	N°1 mm 1038x278 N°1 mm 1038x318	N°1 mm 1338x278 N°1 mm 1338x318
Ruote-Piedi / Castors-Feet	4 Ruote / 4 Castors	4 Ruote / 4 Castors	4 Ruote / 4 Castors
Peso Netto-Lordo / Net-Gross Weight	Kg 155 / 195	Kg 185 / 230	Kg 220 / 270
Voltaggio / Voltage	V 220-240	V 220-240	V 220-240
Frequenza / Frequency	Hz 50	Hz 50	Hz 50
Refrigerante / Refrigerant	R290	R290	R290
Assorbimento / Absorption	W 400	W 445	W 515
Consumo Energia / Energy Consumption	KwH/24H 6,13	KwH/24H 7,56	KwH/24H 8,92