


# BANCHI PASTICCERIA

## PASTRY BENCH



### DELUXE 93 PSV

Banco pasticceria quattro lati vetro ventilato, porte scorrevoli. 3 Ripiani.  
Ventilated positive four-sided glass pastry bench, sliding doors. 3 Shelves.



### DELUXE 123 PSV

Banco pasticceria quattro lati vetro ventilato, porte scorrevoli. 3 Ripiani.  
Ventilated positive four-sided glass pastry bench, sliding doors. 3 Shelves.



### DELUXE 153 PSV

Banco pasticceria quattro lati vetro ventilato, porte scorrevoli. 3 Ripiani.  
Ventilated positive four-sided glass pastry bench, sliding doors. 3 Shelves.





Ripiani: vetro temperato, frontale acciaio  
Shelves: tempered glass, stainless steel front



Porta scorrevole  
Sliding door



Esterno acciaio specchiato, vetro lucido nero  
Body mirror stainless steel, black shiny mirror



Dimensioni mm / Dimensions mm	DELUXE 93 PSV	DELUXE 123 PSV	DELUXE 153 PSV
Dimensioni Esterne (LxPxH) / External Dimensions (WxDxH)	900 x 740 x 1300	1200 x 740 x 1300	1500 x 740 x 1300
Dimensioni Imballo (LxPxH) / Packaging Dimensions (WxDxH)	980 x 830 x 1430	1280 x 830 x 1430	1580 x 830 x 1430
A - Larghezza / Width	840	1140	1440
B - Profondità / Depth	630	630	630
C - Altezza / Height	790	790	790

Caratteristiche Tecniche / Technical Features	DELUXE 93 PSV	DELUXE 123 PSV	DELUXE 153 PSV
Temperatura / Temperature Range	+2 °C / +10 °C	+2 °C / +10 °C	+2 °C / +10 °C
Classe Climatica / Climate Class	4	4	4
Volume Netto-Lordo / Net-Gross Volume	Lt. 415 / 460	Lt. 550 / 610	Lt. 690 / 770
Superficie Esterna Body	Acciaio AISI 304 Stainless steel AISI 304	Acciaio AISI 304 Stainless steel AISI 304	Acciaio AISI 304 Stainless steel AISI 304
Superficie Interna Inner Liner	Acciaio AISI 304 Stainless steel AISI 304	Acciaio AISI 304 Stainless steel AISI 304	Acciaio AISI 304 Stainless steel AISI 304
Termostato / Thermostat	Elettronico / Electronic	Elettronico / Electronic	Elettronico / Electronic
Smart Link WiFi   Controllo remoto / Remote controller	Optional	Optional	Optional
Rumorosità / Noise level	dB 58	dB 61	dB 67
Spessore isolamento / Insulation thickness	mm 45	mm 45	mm 45
Sbrinatorio Defrost	Automatico a fermo compressore Automatic compressor cycle	Automatico a fermo compressore Automatic compressor cycle	Automatico a fermo compressore Automatic compressor cycle
Illuminazione / Lighting	4 Led orizzontali Horizontal	4 Led orizzontali Horizontal	4 Led orizzontali Horizontal
Mensole in vetro temperato (LxP) Tempered glass shelves (WxD)	N°1 mm 738x278 N°2 mm 738 x 318	N°1 mm 1038x278 N°2 mm 1038x318	N°1 mm 1338x278 N°2 mm 1338x318
Ruote-Piedi / Castors-Feet	4 Ruote / 4 Castors	4 Ruote / 4 Castors	4 Ruote / 4 Castors
Peso Netto-Lordo / Net-Gross Weight	Kg 170 / 215	Kg 205 / 255	Kg 245 / 300
Voltaggio / Voltage	V 220-240	V 220-240	V 220-240
Frequenza / Frequency	Hz 50	Hz 50	Hz 50
Refrigerante / Refrigerant	R290	R290	R290
Assorbimento / Absorption	W 410	W 500	W 570
Consumo Energia / Energy Consumption	KwH/24H 7,02	KwH/24H 8,55	KwH/24H 11,01